

# QuantaMesh T3040-LY3

A Powerful  
Spine/Leaf Switch for  
Datacenter and  
Cloud Computing



- 10GBT
- MLAG, OSPF, BGP4, ECMP
- OpenFlow Support
- Network Automation

The QuantaMesh T3040-LY3 is a high performance and low latency layer 2/3/4 Ethernet switch with 40 100BASE-TX/1000BASE-T/10GBASE-T and 8 1/10GBASE-X SFP+ ports in a compact rack unit size. The 40 10GBASE-T ports are backwards compatible with 100/1000M Ethernet networks. The 8 SFP+ ports can aggregate bandwidth up to the core switch. With the energy saving requirements, the QuantaMesh T3040-LY3 is designed with high power efficiency to save OPEX.

## Simplicity

The QuantaMesh T3040-LY3 can be managed through an industry standard command-line interface (CLI) which reduces training and operating costs. A user friendly Web GUI is provided via a standard Web browser for switch management. The QuantaMesh T3040-LY3 also supports Simple Network Management Protocol (SNMP) both from standard MIB and private MIB for easy configuration, monitoring, and management by the network administrator remotely. The Auto-Installation feature implemented in the QuantaMesh T3040-LY3 helps centralized management to simplify deployment of a truly plug-and-play experience. With the evolution from IPv4 to IPv6, the QuantaMesh T3040-LY3 is a IPv6 integrated management device.

## High Availability

The QuantaMesh T3040-LY3 is designed for high availability from both hardware and software perspective. The key features include:

- 1+1 hot-swappable power supplies
- Out-of-band management supported
- 802.1D, 802.1w, and 802.1s supported
- Up to 32 ports per link aggregation group (LACP) and up to 64 groups
- Multi-chassis LAG for preventing the risks of single point failure
- Up to 32 paths ECMP routing for load balancing and redundancy
- Virtual Router Redundancy Protocol supported

## High-Performance L2/L3 access deployments

With the compact 1U form factor, high density 40 100BASE-TX/1000BASE-T/10GBASE-T and 8 1/10GBASE-X SFP+ ports in the front panel, front to back or back to front airflow design, the QuantaMesh T3040-LY3 is ideal for top-of-rack deployments in high-performance, highly demanding datacenters. The 960 gigabits per second switching capacity and 714Mpps forwarding rate with low power consumption make the QuantaMesh T3040-LY3 a powerful solution to aggregate high-performance servers in the datacenter.

## Advanced IPv4 and IPv6 routing

The QuantaMesh T3040-LY3 is a full layer 2 and layer 3 routing switch that supports advanced IPv4 and IPv6 routing features such as RIP v1/v2, OSPF/ECMP, RIPng and OSPFv3. The multicast routing features for IGMP v1/v2/v3, DVMRP, PIM-DM/SM, MLD v1/v2 and PIM-DM6/SM6 are all supported in the QuantaMesh T3040-LY3.

## High Availability

The QuantaMesh T3040-LY3 is an IEEE DCB-based switch delivering a high-performance solution to integrate server edge access. The key features include:

- Congestion Notification (CN, 802.1Qau)
- Enhanced Transmission Selection (ETS, 802.1Qaz)
- Priority-based Flow Control (PFC, 802.1Qbb)
- Datacenter Bridging Extension (DCBX, 802.1Qaz)
- FCoE Initiation Protocol (FIP) snooping

## About QCT

QCT (Quanta Cloud Technology) is a global datacenter solution provider extending the power of hyperscale datacenter design in standard and open SKUs to all datacenter customers. Product lines include servers, storage, network switches, integrated rack systems and cloud solutions, all delivering hyperscale efficiency, scalability, reliability, manageability, serviceability and optimized performance for each workload. QCT offers a full spectrum of datacenter products and services from engineering, integration and optimization to global supply chain support, all under one roof. The parent of QCT is Quanta Computer Inc., a Fortune Global 500 technology engineering and manufacturing company.

## Get a quote: [www.QuantaQCT.com](http://www.QuantaQCT.com)

### United States

QCT LLC., Silicon Valley office  
1010 Rincon Circle, San Jose, CA 95131  
TOLL-FREE: 1-855-QCT-MUST  
TEL: +1-510-270-6111  
FAX: +1-510-270-6161  
Support: +1-510-270-6216

### China

云达科技 北京办公室 (Quanta Cloud Technology)  
Room 1508, East Tower 15F, World Financial Center,  
No.1, East 3rd Ring Zhong Rd., Chaoyang District,  
Beijing, China  
TEL: +86-10-5920-7600  
FAX: +86-10-5981-7958

云达科技 杭州办公室 (Quanta Cloud Technology)  
Room 303, Building No.4, ZheShang Wealth Center,  
No.83, GuDun Rd., Xihu District,  
Hangzhou, Zhejiang, China  
TEL: +86-571-2819-8650

### Japan

Quanta Cloud Technology Japan 株式会社  
Makita Building 3F, 2-5-8, Shibadai-mon, Minato-ku,  
Tokyo 105-0012, Japan  
TEL: +81-3-5777-0818  
FAX: +81-3-5777-0819

### Taiwan

雲達科技 (Quanta Cloud Technology)  
1F, No. 211 Wenhua 2nd Rd., Guishan Dist.,  
Taoyuan City 33377, Taiwan  
TEL: +886-3-286-0707  
FAX: +886-3-327-0001

### Other regions

Quanta Cloud Technology  
No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan  
City 33377, Taiwan  
TEL: +886-3-327-2345  
FAX: +886-3-397-4770

QCT authorized partner

# QuantaMesh T3040-LY3

## Physical ports

- **Port configuration:** 40 100/1000/10GBT and 8 1/10GbE SFP+ ports
- **Management Port:** Out-of-band management port (RJ-45, 10/100/1000Base-T)
- **Console Port:** 1 (RJ-45)
- **USB:** 1 (v 2.0)

## Performance

- **Switching capacity:** 960Gbps
- **Maximum forwarding rate:** 714Mpps
- **Latency:** <3us
- **MAC:** 128K

## L2 Features

- **Switching mode:** store-and-forward
- **Spanning Tree:**
  - 802.1D, 802.1w & 802.1s
  - Fast Forwarding
  - Edge port
  - Loop guard
  - BPDU filter/guard
  - Auto Edge
  - TCN guard
  - Root guard
- **VLAN :**
  - IEEE 802.1Q tagged base
  - Port-Based
  - Private VLAN
  - GVRP/GMRP
  - 802.1v protocol VLAN
  - Voice VLAN
  - MAC-based VLAN
  - IP-subnet VLAN
  - MAC-based Voice VLAN
  - VTP v1/v2
  - QinQ
- **Storm control:**
  - Broadcast
  - Unknown multicast
  - DLF (Unknown unicast)

## IGMP snooping:

- v1/v2/v3
- v1/v2 Querier
- Immediate Leave

## Link Aggregation:

- 802.3ad with LACP (64 groups)
- Static Trunk
- Unicast/Multicast Traffic Balance over Trunking Port
- LACP Fallback

## Multi-chassis LAG (MLAG)

- **Link state**
- **Port backup**
- **Error-Disable Recovery**

## QoS Features

- **Scheduling for priority queue:** WRR, Strict,

- and Hybrid
- **COS:** 802.1p, IP TOS precedence, & DSCP
- **DiffServ**
- **iSCSI optimization**
- **Auto VoIP**
- **Port rate limit**

## Security Features

- **static and dynamic port security (MAC-based)**
- **802.1x:** Port-based, MAC-based, auto VLAN assignment, guest VLAN, unauthenticated VLAN
- **Access Control List:** L2/L3/L4
- **IPv6 ACL:** L3/L4
- **RADIUS:** Authentication and accounting
- **TACACS+:** Authentication
- **HTTPS and SSL:** AES128-cbc, 3ES-cbc, Blowfish-cbc
- **SSH 1.5/V2.0:** AES128-cbc, 3ES-cbc, Blowfish-cbc
- **User name and password:** Local Authentication, Remote Authentication via RADIUS/TACACS+, AAA
- **Denial of Service control**
- **Management IP filtering:** SNMP/Web/Telnet/SSH
- **MAC filtering**
- **IP Source Guard**
- **Dynamic ARP inspection (DAI)**
- **DHCP snooping**
- **Web Authentication (Captive Portal)**

## Management Features

- **Industrial command-line interface**
- **CLI filtering**
- **Web Based Management/HTTPs**
- **Telnet/SSH**
- **Software download/upload:** TFTP, Xmodem, FTP, and SCP/SFTP
- **Configuration download/upload:** TFTP, Xmodem, FTP, and SCP/SFTP
- **Dual Image**
- **SNMP v1/v2c/v3**
- **SNMP inform:** v2/v3
- **RMON 1, 2, 3, & 9**
- **BOOTP:** client/relay
- **DHCP client**
- **DHCP relay**
- **DHCP L2 option 82 Relay**
- **DHCP L3 option 82 Relay**
- **EVENT/Error log:** Local Flash
- **DDNS**
- **DNS client**
- **DNS relay**
- **Remote PING**
- **Traceroute**
- **SNTPv4**
- **LDAP client**
- **LLDP:** 802.1ab
- **CDP**
- **UDLD**
- **Port mirroring:** SPAN
- **sFlow v5**
- **Cable test**
- **Email alerting**
- **CLI scheduler**
- **Auto Install**

## IPv6 Management

- **IPv4/IPv6 Dual Protocol Stack**
- **ICMPv6**
- **ICMPv6 Redirect**
- **IPv6 Path MTU Discovery**
- **IPv6 Neighbor Discovery**
- **Stateless Autoconfiguration**
- **Manual Configuration**
- **DHCPv6**

- **SNMP over IPv6**
- **HTTP over IPv6**
- **SSH over IPv6**
- **IPv6 Telnet Support**
- **IPv6 DNS Resolver**
- **IPv6 RADIUS Support**
- **IPv6 TACACS+ Support**
- **IPv6 Syslog Support**
- **IPv6 SNTP Support**
- **IPv6 TFTP Support**
- **Remote IPv6 Ping**

## Layer 3 Features

- **IP Multinetting/CIDR**
- **/31 subnets**
- **Proxy ARP**
- **IRDP**
- **Static route**
- **RIP v1/v2**
- **OSPF**
- **ECMP**
- **BGP4**
- **IGMP v1/v2/v3**
- **DVMRP**
- **PIM-DM/-SM**
- **VRRP**
- **Source IP configuration**
- **Policy-based routing**

## IPv6 L3 Features

- **Static route**
- **RIPng**
- **OSPFv3**
- **MLD v1/v2**
- **PIM-DM6/-SM6**

## High Availability

- **Redundant power supply:** 1+1

## Data Center Features

- **Congestion Notification (802.1Qau)**
- **Enhanced Transmission Selection (802.1Qaz)**
- **Priority-based Flow Control (802.1Qbb)**
- **DCBX**
- **FCoE Initiation Protocol (FIP) snooping**
- **EVB/802.1Qbg**

## Mechanical

- **Dimension (HxWxD):** 42.8x435x393mm
- **Weight:** 7.9kg/17.42lbs (NET)

## Environmental Specifications

- **Operating temperature:** 0~45°C
- **Operating humidity:** 90% maximum relative humidity

## Electrical

- **Power requirement:** 100~240VAC, 50/60Hz
- **Power consumption:** 376 watts (L2 64B line rate; Cat 6A, 100% fan duty)
- **Safety:** UL, cUL, CB, BSMI, CCC
- **EMC:** CE, FCC, VCCI, BSMI, CCC

## RoHS

- **Reduction of Hazardous Substances (RoHS) 6**

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their representative holders. Copyright © 2014-2015 Quanta Computer Inc. All rights reserved.

